

TITLE OF THE INVENTION

CATHODE-RAY TUBE APPARATUS

CROSS-REFERENCE TO RELATED APPLICATIONS

5 This application is based upon and claims the benefit of priority from the prior Japanese Patent Application No. 2000-183195, filed June 19, 2000, the entire contents of which are incorporated herein by reference.

BACKGROUND OF THE INVENTION

10 The present invention relates generally to a cathode-ray tube apparatus, and more particularly to a color cathode-ray tube apparatus equipped with a velocity modulation coil.

15 There is known a practically used color cathode-ray tube apparatus equipped with a velocity modulation coil for clarifying the contour of an image. The velocity modulation coil is mounted on an outer surface of a neck located behind a deflection yoke, thereby to enhance the sharpness of an image.

20 The velocity modulation coil may be disposed at any position where electron beams will pass, if the whole system is considered. It is necessary, however, to dispose it where no interference of generated magnetic fields will occur between itself and the
25 deflection yoke. Accordingly, there is no choice but to dispose the velocity modulation coil at a predetermined position on the cathode side of an anode

electrode.

Taking the above into account, the velocity modulation coil is normally disposed around a location where a focus electrode is provided. In this case, however, the frequency of current flowing in the velocity modulation coil is high, and a magnetic field generated from the velocity modulation coil causes an eddy current in the focus electrode. Since the eddy current suppresses generation of a magnetic flux of the velocity modulation coil, which acts in the focus electrode, the velocity modulation effect is disadvantageously reduced.

In order to intensify the magnetic field of the velocity modulation coil, two methods are available: to increase the current flowing in the velocity modulation coil, or to increase the number of turns of the velocity modulation coil. In the case of the former, the diameter of wire of the coil needs to be increased, and a greater power consumption is required to supply a greater current. As a result, a load on the circuit, as well as the cost, will increase. In the case of the latter, the thickness of the velocity modulation coil increases, and the adjustment performance for a purity convergence magnet deteriorates. Although the magnetic field can theoretically be intensified by adjusting the position of the velocity modulation coil, the position of the coil cannot freely be changed because of

positioning restrictions on actual design, as mentioned above. Besides, in general terms, if a magnetic field for correcting the contour of an image is intensified by some method, the action of the magnetic field on
5 electron beams increases and the amount of a leak magnetic field also increases. Consequently, a problem of an electromagnetic wave fault may arise.

On the other hand, there are known electron gun structures, as disclosed in Jpn. Pat. Appln. KOKOKU
10 Publication No. 62-21216, etc., which embody a method of causing a magnetic field of the velocity modulation coil to effectively act on electron beams, without intensifying this magnetic field. In these structures, an electrode in a region where the velocity modulation
15 coil is positioned, which is normally a single electrode or an integral electrode of tightly welded plural electrode components, is divided into electrode members with spaces provided thereamong, and these electrode members are electrically connected by means
20 of lead wire.

The spaces among the divided electrode members of the electrode function to suppress an eddy current caused in the electrode by the magnetic field of the velocity modulation coil, and to let the magnetic field
25 of the velocity modulation coil permeate into the electrode and act on the electron beams, thus enhancing the velocity modulation effect. In this method,

however, a welding work for lead wire is necessary in order to electrically connect the electrode members of the electrode. There is a possibility of a problem of work efficiency and deformation of the electrode members at the time of welding lead wire. Moreover, since the electrode members are spaced apart, the strength of holding of the electrode members may become deficient, the electrode members may be displaced relative to the axial direction, or the electric field from the inner wall of the neck may permeate.

Jpn. Pat. Appln. KOKAI Publication No. 10-172464, etc. disclose electron gun structures as other countermeasures. In the methods according to these countermeasures, slits are formed in an electrode in a region where the velocity modulation coil is positioned. The slits function to suppress an eddy current caused in the electrode, and to let the magnetic field of the velocity modulation coil permeate into the electrode via the slits and act on the electron beams, thus enhancing the velocity modulation effect. In these methods, however, the formation of the slits may decrease the strength of the electrode, degrade the precision in dimension of the electrode, e.g. circularity of electron beam passage holes, and give rise to deformation of the electrode at the time of assembly.

As has been mentioned above, in order to obtain an

image with high sharpness, it is necessary to cause the magnetic field of the velocity modulation coil to effectively act on the electron beams. However, this magnetic field causes an eddy current in the electrode of the electron gun assembly, and the eddy current suppress the magnetic field of the velocity modulation coil and degrades the velocity modulation effect.

In order to solve these problems, there are the prior-art methods wherein an electrode in a region where the velocity modulation coil is positioned, which is normally a single electrode or an integral electrode of tightly welded plural electrode components, is divided into electrode members with spaces provided thereamong, and these electrode members are electrically connected by means of lead wire, or wherein slits are formed in an electrode in a region where the velocity modulation coil is positioned. These methods, however, have the problems in that the precision in dimension of the electrode deteriorates or the electrode may deform due to the decrease in strength of the electrode, and the electric field of the neck may permeate.

BRIEF SUMMARY OF THE INVENTION

The present invention has been made in consideration of the above problems, and an object of the invention is to provide a cathode-ray tube apparatus capable of suppressing a decrease in velocity

modulation effect, without increasing a magnetic field of a velocity modulation coil. Another object of the invention is to provide a cathode-ray tube apparatus capable of providing an image with high sharpness while preventing a decrease in the precision of dimension of an electrode of an electron gun assembly and deformation of the electrode, without degrading the strength of the electrode and the work efficiency of assembling the electrode.

10 The present invention provides a cathode-ray tube apparatus comprising:

 an electron gun assembly having a plurality of electrodes constituting an electron beam generating section for generating electron beams and a main lens section for focusing the electron beams, which have been generated from the electron beam generating section, onto a phosphor screen;

 a deflection yoke for generating deflection magnetic fields for deflecting the electron beams emitted from the electron gun assembly in a horizontal direction and a vertical direction of the phosphor screen, and causing the electron beams to scan the phosphor screen in the horizontal and vertical directions; and

25 velocity modulation coils for modulating scan velocities of the electron beams,

 wherein at least one of the electrodes of the

electron gun assembly is constructed by coupling at least first and second electrode members arranged in a direction of passing of the electron beams, and

the first electrode member has a projecting
5 portion on an end face thereof, which is to be coupled to the second electrode member disposed adjacent to the first electrode member.

Additional objects and advantages of the invention will be set forth in the description which follows, and
10 in part will be obvious from the description, or may be learned by practice of the invention. The objects and advantages of the invention may be realized and obtained by means of the instrumentalities and combinations particularly pointed out hereinafter.

15 BRIEF DESCRIPTION OF THE SEVERAL VIEWS OF THE DRAWING

The accompanying drawings, which are incorporated in and constitute a part of the specification, illustrate presently preferred embodiments of the invention, and together with the general description
20 given above and the detailed description of the preferred embodiments given below, serve to explain the principles of the invention.

FIG. 1 is a horizontal cross-sectional view schematically showing an example of the structure of a
25 cathode-ray tube apparatus of the present invention;

FIG. 2 is a horizontal cross-sectional view showing an example of an electron gun assembly applied

to the cathode-ray tube apparatus shown in FIG. 1;

FIG. 3A is a plan view schematically showing the structure of an electrode member applied to a third grid of the electron gun assembly shown in FIG. 2;

5 FIG. 3B is a perspective view schematically showing the structure of the electrode member shown in FIG. 3A;

10 FIG. 4 is a horizontal cross-sectional view showing another example of the electron gun assembly applied to the cathode-ray tube apparatus shown in FIG. 1;

FIG. 5A is a plan view schematically showing the structure of an electrode member applied to a third grid of the electron gun assembly shown in FIG. 4;

15 FIG. 5B is a perspective view schematically showing the structure of the electrode member shown in FIG. 5A;

20 FIG. 6 shows the disposition of a velocity modulation coil applied to the cathode-ray tube apparatus shown in FIG. 1; and

FIGS. 7A to 7D illustrate the operation of the velocity modulation coil.

DETAILED DESCRIPTION OF THE INVENTION

25 Embodiments of a cathode-ray tube apparatus according to the present invention will now be described with reference to the accompanying drawings.

As is shown in FIG. 1, the cathode-ray tube

apparatus of the present invention, for example, a self-convergence type in-line color cathode-ray tube apparatus, comprises an envelope formed of a panel 1, a neck 5 and a funnel 2 integrally coupled to the panel 1 and neck 5. The panel 1 has a phosphor screen 4 on its inner surface. The phosphor screen 4 comprises stripe-shaped or dot-shaped three-color phosphor layers that emit blue, green and red light. A shadow mask 3, which has many apertures therein, is disposed to face the phosphor screen 4. An in-line electron gun assembly 6 is included in the neck 5. The electron gun assembly 6 emits three electron beams 7B, 7G and 7R arranged in line, i.e. a center beam 7G and a pair of side beams 7B and 7R passing in the same horizontal plane. A deflection yoke 8 is mounted on that portion of the funnel 2, which extends between a large-diameter portion of the funnel 2 and the neck 5. The deflection yoke 8 generates non-uniform deflection magnetic fields for deflecting the three electron beams 7B, 7G and 7R from the electron gun assembly 6 in a horizontal direction (X) and a vertical direction (Y). The non-uniform deflection magnetic fields comprise a pin-cushion-shaped horizontal deflection magnetic field and barrel-shaped vertical deflection magnetic field. The cathode-ray tube apparatus has a pair of velocity modulation coils 9 mounted on an outer surface of the neck 5 behind the deflection yoke 8. As is shown in

FIG. 1, the velocity modulation coils 9 are horizontally disposed to be opposed to each other.

The three electron beams 7B, 7G and 7R emitted from the electron gun assembly 6 are deflected by the non-uniform magnetic fields generated by the deflection yoke 8 and caused to scan the phosphor screen 4 via the shadow mask 3 in the horizontal direction X and vertical direction Y. Thereby, a color image is displayed.

For reasons of the outside space of the neck 5, the velocity modulation coils 9 applied to this cathode-ray tube apparatus are attached inside a cylindrical support 13 for supporting a purity convergence magnet 12, as shown in FIG. 6. A pair of annular purity adjustment magnets and two pairs of annular convergence adjustment magnets, which constitute the purity convergence magnet 12, are rotatably disposed around the velocity modulation coils 9.

The velocity modulation coils 9 operate, as will be described below.

A video signal 17 with a waveform shown in FIG. 7A is subjected to first-order differential. Thus, a pulse current 18 having peaks at a rising portion and a falling portion of the video signal, as shown in FIG. 7B, is obtained. The pulse current 18 is supplied to the velocity modulation coils 9, thereby causing the

velocity modulation coils 9 to generate a magnetic field. The magnetic field generated by the velocity modulation coils 9 is combined with the horizontal deflection magnetic field generated by the deflection yoke 8, and a composite magnetic field 19, as shown in FIG. 7C, is formed. If the composite magnetic field 19 is subjected to first-order differential, a curve 20 shown in FIG. 7D is obtained. The scan velocity of a horizontally deflected electron beam is proportional to the variation of the magnetic field. Accordingly, the horizontal scan velocity of the electron beam varies, as indicated by the curve 20. Specifically, in a first half time period T1 of the rising portion (changing from black to white) of the video signal, the scan velocity is increased to lower the luminance of the image. In a second half time period T2, the scan velocity is decreased to raise the luminance of the image. In the falling portion (changing from white to black) of the video signal, the scan velocity varies reverse to the case of the rising portion. Thereby, the contours of the rising and falling portions of the display image are corrected, and the sharpness of the image is enhanced.

As is shown in FIG. 2, the electron gun assembly 6 comprises three cathodes K arranged in line in the horizontal direction X, three heaters (not shown) for individually heating the cathodes K, and four grids,

i.e. a first grid G1, a second grid G2, a third grid G3 and a fourth grid G4. The four grids are successively arranged in a tube axis direction Z from the cathodes K toward the phosphor screen 4. The third grid G3 comprises a first segment G3-1 and a second segment G3-2, which are arranged in the named order from the cathode K side. The heaters, cathodes K and the four grids are integrally fixed by a pair of insulating supports.

10 Each of the first and second grids G1 and G2 is composed of a plate-like electrode with an integral structure. The plate-like electrode has three circular electron beam passage holes horizontally arranged in line in association with the three cathodes K.

15 The third grid G3 functioning as a focus electrode is constructed by coupling a plurality of electrode members, that is, the mutually adjacent first segment G3-1 and second segment G3-2. The first segment G3-1 and second segment G3-2 are composed of cylindrical electrodes, respectively. Each cylindrical electrode
20 has three circular electron beam passage holes horizontally arranged in line in association with the three cathodes K.

 The fourth grid G4 functioning as an anode
25 electrode is composed of a cup-shaped electrode. The cup-shaped electrode has, in its surface facing the third grid G3, three circular electron beam passage

holes horizontally arranged in line in association with the three cathodes K.

5 The velocity modulation coils 9 are mounted on an outer surface of the neck at a region where the third grid G3 is disposed.

10 In the electron gun assembly having the above-described structure, a voltage obtained by superimposing a modulation signal corresponding to the video signal on a DC voltage of about 100V to 200V is applied to the cathodes K. The first grid G1 is grounded. A DC voltage of about 500V to 1000V is applied to the second grid G2. A constant focus voltage V_f of about 6 kV to 10 kV is applied to the third grid G3. An ultimate acceleration voltage E_b of about 22 kV to 35 kV is applied to the fourth grid G4.

15 The cathodes K, first grid G1 and second grid G2 constitute an electron beam generating section for generating electron beams. The second grid G2 and third grid G3 constitute a prefocus lens for prefocusing the electron beams generated from the electron beam generating section. The third grid G3 and fourth grid G4 constitute a main lens for ultimately focusing the prefocused electron beams on the phosphor screen.

25 The first segment G3-1 and second segment G3-2 of the third grid G3 have a plurality of projecting portions 10 at their mutually coupled end faces, as

shown in FIGS. 3A and 3B. Specifically, the first segment G3-1 has plural projecting portions 10 at its end face opposed to the second segment G3-2. The second segment G3-2 has plural projecting portions 10 at its end face opposed to the first segment G3-1 such that these projecting portions 10 correspond to the projecting portions 10 of the first segment G3-1. The first segment G3-1 and second segment G3-2 are coupled by welding their projecting portions 10.

The projecting portions 10 of these electrode members are formed at regions where the magnetic field generated by the velocity modulation coils 9 does not act on the electron beams. Referring to FIG. 3A, assume that a maximum diametrical dimension of the electron beam passage hole 11 in the horizontal direction including the center axis C of the passage hole 11 is 100%. If each projecting portion 10 is formed within a predetermined region (where the electron beam will mainly pass) corresponding to 50% of the maximum diametrical dimension (100%), with the center of this 50% dimension being set at the center axis C of the passage hole 11, the eddy current suppression effect will gradually decrease as the location of the projecting portion 10 becomes closer to the center axis C. If each projecting portion 10 is formed in a region outside the 50% dimension, the eddy current suppression effect will gradually increase as

it is located away from the region of 50% dimension.
In short, if the maximum horizontal diametrical
dimension of the electron beam passage hole 11 is D , it
is desirable that the projecting portion 10 be located
5 within a region corresponding to $4/D$ from the end of
the passage hole 11 toward the center axis C .

Thereby, the projecting portion 10 does not block
the passage of the magnetic field acting on the
electron beam in the vertical direction Y , which passes
10 through the electron beam passage hole 11. Accordingly,
the magnetic field generated by the velocity modulation
coils 9 can be made to effectively act on the electron
beams, and degradation of the velocity modulation
effect can be suppressed.

15 In this case, the effect of suppressing the eddy
current due to the magnetic field generated by the
velocity modulation coils 9 was increased 1.3 times,
compared to the case of a color CRT apparatus in which
electrode members are not coupled by means of the
20 projections 10.

As has been described above, since the electrodes
of the electron gun assembly have the above-described
structure, the generation of the eddy current in the
electrode due to the magnetic field from the velocity
25 modulation coils 9 can be suppressed. The magnetic
field generated by the velocity modulation coils 9 can
easily permeate through the gaps between the electrode

members coupled by means of the projecting portions 10, and it effectively acts on the electron beams. Thus, a sufficient velocity modulation effect can be obtained. Moreover, there is no need to modify the conventional assembly steps of the electron gun assembly. Since the electrode members constituting the electrode are machined and directly coupled, the mechanical strength of the electrode can be increased, and misalignment of the electrode members relative to the tube axis can be prevented. Furthermore, there is no need to perform lead wire welding for electrically connecting the divided electrode members, which may result in deformation of the electrode. Besides, the projecting portions formed on the electrode members can suppress permeation of the neck electric field.

Another embodiment of the invention will now be described.

As is shown in FIG. 4, the electron gun assembly of this embodiment is substantially the same as the electron gun assembly shown in FIG. 2 except for the structure of the third grid G3. Accordingly, the common structural elements are denoted by like reference numerals and a detailed description thereof is omitted.

In the preceding embodiment, the projecting portions 10 are formed in truncated conical shapes at predetermined regions. In the present embodiment, as

shown in FIGS. 5A and 5B, the projecting portions 10 are formed in stripe shapes on both sides of each electron beam passage hole 11. The stripe-shaped projecting portions 10, too, are disposed outside the regions where the magnetic field generated by the velocity modulation coils 9 acts on the electron beams.

With this structure, the eddy current caused in the third grid G3 by the magnetic field from the velocity modulation coils 9 can be reduced by the coupling portion with the projecting portions 10 within the third grid G3. Part of the magnetic field from the velocity modulation coils 9 permeates into the third grid G3 through the gaps at the coupling portion, thereby acting on the electron beams and achieving an effective velocity modulation action. Thus, degradation in velocity modulation effect can be suppressed and an image with high sharpness can be obtained.

In the above-described embodiments, only one coupling interface is provided between the electrode members with the projecting portions within the electrode. However, if the number of electrode members can be increased within the tolerable design range of the electrode length, the number of coupling interfaces may be increased accordingly. In the embodiments, the projecting portions provided at the coupling interface are formed on both the electrode members to be coupled.

However, the projecting portions provided at the coupling interface may be formed on only one of the electrode members to be coupled. There is no need to couple the electrode members using the projecting portions formed on both the coupling surfaces of the electrode members. The electrode members may be coupled using the projecting portions formed on one of the coupling surfaces of the electrode members.

The above-described embodiments are directed to color cathode-ray tube apparatuses each having a bi-potential electron gun assembly. However, the present invention is applicable to various types of color cathode-ray tube apparatuses having a uni-potential electron gun assembly, a bi-potential/uni-potential composite electron gun assembly, and a high-uni-potential electron gun assembly, etc.

As has been described above, the present invention can provide a cathode-ray tube apparatus capable of suppressing a decrease in velocity modulation effect, without increasing a magnetic field of a velocity modulation coil. This invention can also provide a cathode-ray tube apparatus capable of providing an image with high sharpness while preventing a decrease in the precision of dimension of an electrode of an electron gun assembly and deformation of the electrode, without degrading the strength of the electrode and the work efficiency of assembling the electrode.

Additional advantages and modifications will readily occur to those skilled in the art. Therefore, the invention in its broader aspects is not limited to the specific details and representative embodiments shown and described herein. Accordingly, various
5 modifications may be made without departing from the spirit or scope of the general inventive concept as defined by the appended claims and their equivalents.

117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841
842
843
844
845
846
847
848
849
850
851
852
853
854
855
856
857
858
859
860
861
862
863
864
865
866
867
868
869
870
871
872
873
874
875
876
877
878
879
880
881
882
883
884
885
886
887
888
889
890
891
892
893
894
895
896
897
898
899
900
901
902
903
904
905
906
907
908
909
910
911
912
913
914
915
916
917
918
919
920
921
922
923
924
925
926
927
928
929
930
931
932
933
934
935
936
937
938
939
940
941
942
943
944
945
946
947
948
949
950
951
952
953
954
955
956
957
958
959
960
961
962
963
964
965
966
967
968
969
970
971
972
973
974
975
976
977
978
979
980
981
982
983
984
985
986
987
988
989
990
991
992
993
994
995
996
997
998
999
1000
1001
1002
1003
1004
1005
1006
1007
1008
1009
1010
1011
1012
1013
1014
1015
1016
1017
1018
1019
1020
1021
1022
1023
1024
1025
1026
1027
1028
1029
1030
1031
1032
1033
1034
1035
1036
1037
1038
1039
1040
1041
1042
1043
1044
1045
1046
1047
1048
1049
1050
1051
1052
1053
1054
1055
1056
1057
1058
1059
1060
1061
1062
1063
1064
1065
1066
1067
1068
1069
1070
1071
1072
1073
1074
1075
1076
1077
1078
1079
1080
1081
1082
1083
1084
1085
1086
1087
1088
1089
1090
1091
1092
1093
1094
1095
1096
1097
1098
1099
1100
1101
1102
1103
1104
1105
1106
1107
1108
1109
1110
1111
1112
1113
1114
1115
1116
1117
1118
1119
1120
1121
1122
1123
1124
1125
1126
1127
1128
1129
1130
1131
1132
1133
1134
1135
1136
1137
1138
1139
1140
1141
1142
1143
1144
1145
1146
1147
1148
1149
1150
1151
1152
1153
1154
1155
1156
1157
1158
1159
1160
1161
1162
1163
1164
1165
1166
1167
1168
1169
1170
1171
1172
1173
1174
1175
1176
1177
1178
1179
1180
1181
1182
1183
1184
1185
1186
1187
1188
1189
1190
1191
1192
1193
1194
1195
1196
1197
1198
1199
1200
1201
1202
1203
1204
1205
1206
1207
1208
1209
1210
1211
1212
1213
1214
1215
1216
1217
1218
1219
1220
1221
1222
1223
1224
1225
1226
1227
1228
1229
1230
1231
1232
1233
1234
1235
1236
1237
1238
1239
1240
1241
1242
1243
1244
1245
1246
1247
1248
1249
1250
1251
1252
1253
1254
1255
1256
1257
1258
1259
1260
1261
1262
1263
1264
1265
1266
1267
1268
1269
1270
1271
1272
1273
1274
1275
1276
1277
1278
1279
1280
1281
1282
1283
1284
1285
1286
1287
1288
1289
1290
1291
1292
1293
1294
1295
1296
1297
1298
1299
1300
1301
1302
1303
1304
1305
1306
1307
1308
1309
1310
1311
1312
1313
1314
1315
1316
1317
1318
1319
1320
1321
1322
1323
1324
1325
1326
1327
1328
1329
1330
1331
1332
1333
1334
1335
1336
1337
1338
1339
1340
1341
1342
1343
1344
1345
1346
1347
1348
1349
1350
1351
1352
1353
1354
1355
1356
1357
1358
1359
1360
1361
1362
1363
1364
1365
1366
1367
1368
1369
1370
1371
1372
1373
1374
1375
1376
1377
1378
1379
1380
1381
1382
1383
1384
1385
1386
1387
1388
1389
1390
1391
1392
1393
1394
1395
1396
1397
1398
1399
1400
1401
1402
1403
1404
1405
1406
1407
1408
1409
1410
1411
1412
1413
1414
1415
1416
1417
1418
1419
1420
1421
1422
1423
1424
1425
1426
1427
1428
1429
1430
1431
1432
1433
1434
1435
1436
1437
1438
1439
1440
1441
1442
1443
1444
1445
1446
1447
1448
1449
1450
1451
1452
1453
1454
1455
1456
1457
1458
1459
1460
1461
1462
1463
1464
1465
1466
1467
1468
1469
1470
1471
1472
1473
1474
1475
1476
1477
1478
1479
1480
1481
1482
1483
1484
1485
1486
1487
1488
1489
1490
1491
1492
1493
1494
1495
1496
1497
1498
1499
1500
1501
1502
1503
1504
1505
1506
1507
1508
1509
1510
1511
1512
1513
1514
1515
1516
1517
1518
1519
1520
1521
1522
1523
1524
1525
1526
1527
1528
1529
1530
1531
1532
1533
1534
1535
1536
1537
1538
1539
1540
1541
1542
1543
1544
1545
1546
1547
1548
1549
1550
1551
1552
1553
1554
1555
1556
1557
1558
1559
1560
1561
1562
1563
1564
1565
1566
1567
1568
1569
1570
1571
1572
1573
1574
1575
1576
1577
1578
1579
1580
1581
1582
1583
1584
1585
1586
1587
1588
1589
1590
1591
1592
1593
1594
1595
1596
1597
1598
1599
1600
1601
1602
1603
1604
1605
1606
1607
1608
1609
1610
1611
1612
1613
1614
1615
1616
1617
1618
1619
1620
1621
1622
1623
1624
1625
1626
1627
1628
1629
1630
1631
1632
1633
1634
1635
1636
1637
1638
1639
1640
1641
1642
1643
1644
1645
1646
1647
1648
1649
1650
1651
1652
1653
1654
1655
1656
1657
1658
1659
1660
1661
1662
1663
1664
1665
1666
1667
1668
1669
1670
1671
1672
1673
1674
1675
1676
1677
1678
1679
1680
1681
1682
1683
1684
1685
1686
1687
1688
1689
1690
1691
1692
1693
1694
1695
1696
1697
1698
1699
1700
1701
1702
1703
1704
1705
1706
1707
1708
1709
1710
1711
1712
1713
1714
1715
1716
1717
1718
1719
1720
1721
1722
1723
1724
1725
1726
1727
1728
1729
1730
1731
1732
1733
1734
1735
1736
1737
1738
1739
1740
1741
1742
1743
1744
1745
1746
1747
1748
1749
1750
1751
1752
1753
1754
1755
1756
1757
1758
1759
1760
1761
1762
1763
1764
1765
1766
1767
1768
1769
1770
1771
1772
1773
1774
1775
1776
1777
1778
1779
1780
1781
1782
1783
1784
1785
1786
1787
1788
1789
1790
1791
1792
1793
1794
1795
1796
1797
1798
1799
1800
1801
1802
1803
1804
1805
1806
1807
1808
1809
1810
1811
1812
1813
1814
1815
1816
1817
1818
1819
1820
1821
1822
1823
1824
1825
1826
1827
1828
1829
1830
1831
1832
1833
1834
1835
1836
1837
1838
1839
1840
1841
1842
1843
1844
1845
1846
1847
1848
1849
1850
1851
1852
1853
1854
1855
1856
1857
1858
1859
1860
1861
1862
1863
1864
1865
1866
1867
1868
1869
1870
1871
1872
1873
1874
1875
1876
1877
1878
1879
1880
1881
1882
1883
1884
1885
1886
1887
1888
1889
1890
1891
1892
1893
1894
1895
1896
1897
1898
1899
1900
1901
1902
1903
1904
1905
1906
1907
1908
1909
1910
1911
1912
1913
1914
1915
1916
1917
1918
1919
1920
1921
1922
1923
1924
1925
1926
1927
1928
1929
1930
1931
1932
1933
1934
1935
1936
1937
1938
1939
1940
1941
1942
1943
1944
1945
1946
1947
1948
1949
1950
1951
1952
1953
1954
1955
1956
1957
1958
1959
1960
1961
1962
1963
1964
1965
1966
1967
1968
1969
1970
1971
1972
1973
1974
1975
1976
1977
1978
1979
1980
1981
1982
1983
1984
1985
1986
1987
1988
1989
1990
1991
1992
1993
1994
1995
1996
1997
1998
1999
2000
2001
2002
2003
2004
2005
2006
2007
2008
2009
2010
2011
2012
2013
2014
2015
2016
2017
2018
2019
2020
2021
2022
2023
2024
2025
2026
2027
2028
2029
2030
2031
2032
2033
2034
2035
2036
2037
2038
2039
2040
2041
2042
2043
2044
2045
2046
2047
2048
2049
2050
2051
2052
2053
2054
2055
2056
2057
2058
2059
2060
2061
2062
2063
2064
2065
2066
2067
2068
2069
2070
2071
2072
2073
2074
2075
2076
2077
2078
2079
2080
2081
2082
2083
2084
2085
2086
2087
2088
2089
2090
2091
2092
2093
2094
2095
2096
2097
2098
2099
2100
2101
2102
2103
2104
2105
2106
2107
2108
2109
2110
2111
2112
2113
2114
2115
2116
2117
2118
2119
2120
2121
2122
2123
2124
2125
2126
2127
2128
2129
2130
2131
2132
2133
2134
2135
2136
2137
2138
2139
2140
2141
2142
2143
2144
2145
2146
2147
2148
2149
2150
2151
2152
2153
2154
2155
2156
2157
2158
2159
2160
2161
2162
2163
2164
2165
2166
2167
2168
2169
2170
2171
2172
2173
2174
2175
2176
2177
2178
2179
2180
2181
2182
2183
2184
2185
2186
2187
2188
2189
2190
2191
2192
2193
2194
2195
2196
2197
2198
2199
2200
2201
2202
2203
2204
2205
2206
2207
2208
2209
2210
2211
2212
2213
2214
2215
2216
2217
2218
2219
2220
2221
2222
2223
2224
2225
2226
2227
2228
2229
2230
2231
2232
2233
2234
2235
2236
2237
2238
2239
2240
2241
2242
2243
2244
2245
2246
2247
2248
2249
2250
2251
2252
2253
2254
2255
2256
2257
2258
2259
2260
2261
2262
2263
2264
2265
2266
2267
2268
2269
2270
2271
2272
2273
2274
2275
2276
2277
2278
2279
2280
2281
2282
2283
2284
2285
2286
2287
2288
2289
2290
2291
2292
2293
2294
2295
2296
2297
2298
2299
230